BOG 5: Software Development Methodologies

ASCR Workshop on Extreme Heterogeneity in HPC 23-25 Jan 2018

BOG 5 Contributors

Moderator(s): Sherry Li, David Bernholdt, Anshu Dubey

BOGists:

- Michelle Strout
- Richard Lethin
- Rob Falgout
- Tiffany Mintz
- Line Pouchard
- Keita Teranishi
- Brian van Straalen
- Bob Lucas
- George Biros
- Meifeng Lin

- Stan Tomov
- Seyong Lee
- Edmund Chow
- Mary Hall
- Clara Leckey
- Bob Colwell
- Uzi Vishkin
- Andrew Lumsdaine

BOG 5 Charge

The purpose of the breakout session is to brainstorm and discuss capabilities that will be needed in the 2025-2035 timeframe to make increasingly heterogeneous hardware technologies useful and productive for science applications.

Outcome: Identify a list (<= 5?) of priority research directions in the area of software development methodologies (SDM), in the 2030+ timeframe.

BOG 5 discussion scope

Methodologies, tools, and processes that promote the productivity of software developers and sustainability of software artifacts

- Programmability and usability: design easy-to-use user interfaces for efficient use of underlying hardware.
- Composability and interoperability: support the need of a single application using multiple software components developed by different teams.
- **Sustainability and maintainability**: maintain the capabilities of a software product over its intended life span, including modifying a software product's behavior to reflect new architectural advances.
- Portability (to be addressed in BOG #11, Thursday)

SDM FSD: Status and Recent Advances (1/3)

In last 3-4 years, significant progress has been made through IDEAS project (https://ideas-productivity.org) (continue into ECP):

- Jointly funded by ASCR and BER.
- Developed productivity and sustainability principles and guidelines to meet the needs of BER use cases in next-generation multiscale and multiphysics modeling of terrestrial ecosystems.
- Two SDM focus areas:
 - Methodologies and "How To"
 - xSDK: Extreme-Scale Scientific Software Development Kit

IDEAS Results: Methodologies (2/3)

Formalizing and standardizing systematic approaches for SDM.

- "What Is" and "How To" documents to promote best practices.
 https://ideas-productivity.org/resources/howtos/
 - What is CSE software productivity?
 - What is software configuration?
 - What is performance portability?
 - What is CSE software testing?
 - What are software testing practices?
 - What is good documentation?
 - What are interoperable software libraries?
 - What is version control?
 -

- How to configure software?
- How to enable performance portability?
- How to add and improve testing in CSE software project?
- How to write good documentation?
- How to do version control with git?
-

Outreach: webinars, tutorials, etc.

IDEAS Results: xSDK https://xsdk.info (3/3)

Addressing the end user's productivity bottleneck: handling incompatibilities among different packages.

- A collection of related and complementary numerical libraries
 - o Hypre, MAGMA, MFEM, PETSc, SUNDIALS, SuperLU, Trilinos
- Community policies help to improve SW quality and promote interoperability.

https://xsdk.info/policies

- xSDK Community Package Policies
- o xSDK Community Installation Policies: GNU Autoconf and CMake Options

xSDK Package Policies

xSDK compatible package: Must satisfy mandatory xSDK policies:

- **M1.** Support xSDK community GNU Autoconf or CMake options.
- **M2.** Provide a comprehensive test suite.
- **M3.** Employ user-provided MPI communicator.
- **M4**. Give best effort at portability to key architectures.
- **M5.** Provide a documented, reliable way to contact the development team.
- **M6.** Respect system resources and settings made by other previously called packages.
- **M7.** Come with an open source license.
- **M8.** Provide a runtime API to return the current version number of the software.
- **M9.** Use a limited and well-defined symbol, macro, library, and include file name space.
- **M10.** Provide an accessible repository (not necessarily publicly available).
- **M11.** Have no hardwired print or IO statements.
- **M12.** Allow installing, building, and linking against an outside copy of external software.
- **M13.** Install headers and libraries under refix>/include/ and fix>/lib/.
- **M14.** Be buildable using 64 bit pointers. 32 bit is optional.
- **M15.** All xSDK compatibility changes should be sustainable.
- **M16.** The package must support production-quality installation compatible with the xSDK install tool and xSDK metapackage.

SDM FSD: Challenges and Opportunities

Software modularity to support

- Multiple accelerators organized in different NUMA domains
- New design of hierarchical encapsulation and abstraction
- Nested parallelism at different levels of hierarchy
- New data structures and algorithms that better exploit various hardware components

Extend xSDK methodologies beyond mathematical software

- Interoperability between different programming models: eg., MPI and PGAS
- Community policies to support the use of multiple programming models in a single executable

Autotuning in a heterogeneous environment

- In addition to algorithm parameters, many more architectural parameters need be considered in the optimization process. How to reduce parameter search space?
- Autotuning accuracy depends on a stable and reproducible computing environment. How to handle large variability of time measurement due to various resource sharing?

Discussion: list of key research challenges

- 1. Productive programming requires an abstract machine model to code to. But is an AMM a meaningful concept in an EH world? Does every different compute unit need a different AMM? Is there a meaningful higher level?
- 2. We need opportunities to experiment extensively to develop the experience to guide software architecture and other choices. Need applications engaged in this too.
- 3. How do we think about reproducibility in an EH world? Bitwise reproducibility and threshold error bounds is already not an option in many cases. Can we develop a more robust understanding of how to evaluate the correctness of code?
- 4. How do we test thoroughly in a world where there are many possible backends?
- 5. Are there opportunities for AI/ML to assist with writing of code or code generation?
- 6. Can we use AI/ML to better understand the behavior of the underlying hardware to better inform developers?
- 7. Code/libraries are too large to "port". Can we drive towards smaller, finer granularity, more easily portable units? Abstraction lifting

For other groups

- Much discussion of performance counters (perf. port. BOG 11, OS/R BOG 10)
 - Need them in hardware
 - Need access to them (via the OS)
 - Need to be able to collect and capture the info
 - Want to be able to use all of this information for (AI/ML) based autotuning
 - Software modules don't have the say way of using/reporting perf info
 - EH comes in because
 - Different teams are providing different information about different processors
 - We will need to pull together much more, and much more diverse, info to understand performance
 - Performance at component level doesn't imply performance at global level
- Configure/build/tune is an important workflow that needs to be addressed
 - Typical system configurations at facilities may not be supporting this well enough.
 - System configuration/admin (BOG 8), productivity (BOG 9)

Discussion: Possible Research Directions Summary

1.

PRD X.n : Short title of possible research direction

- One paragraph description (3 sentence/bullet)
- Research challenges
 - Metrics for progress
- Potential research approaches and research directions
- How and when will success impact technology?